



# PUSH BUTTON - TYPE SPEECH OUTPUT

## TECHNICAL DATA SHEET

### HOUSING

Material	Polycarbonate
Colour	RAL 1007 yellow, (on request - blue RAL 5017)
Dimensions	180 mm/ 68 mm / 57 mm
	
Weight	600 g - 900 g (depending on the length of the cable)
Operating altitude (MAMSL)	up to 2000 m
Temperatur Range ( °C )	min. -40°C / max. +70°C
Protection Class	Class II
IP Classification	IP 55
IK Rating	IK 09
Compliance with standards	DIN 32981:2018-06 DIN EN 50556:2019-03 (VDE 0832-100) DIN EN 50293:2013-02 (VDE 0832-100) RILSA 2015 DIN EN 62368-1:2016-05



DESCRIPTION	SPEECH OUTPUT 8 Ohm	SPEECH OUTPUT 100V
Item number	1682	1681
Voltage	8 Ohm Audio emplifier	100V from Audio emplifier
Speech output	loudspeaker	audio transformer and loudspeaker
Request		
Rated load-carrying capacity	2 W	2 W



# PUSH BUTTON - TYPE SPEECH OUTPUT

DESCRIPTION	SPEECH OUTPUT 8 Ohm	SPEECH OUTPUT 100V
Rated music-carrying capacity	3 W	3 W
Rated Impedance	8 Ohm	Transformer 100V
Frequency response	180 - 17.000 Hz	180 - 17.000 Hz

## ACCESSORIES (SEPARATELY ORDER)

<p><b>Metal protection guard</b> (Stainless steel)</p>	<p>To protect the push button against vandalism.</p> 
<p><b>Rubber gasket flat</b> Item no. 12021</p>	<p>For attaching the push button on the flat surfaces (for example wall).</p> 
<p><b>Adapter plate</b> (Stainless steel) Item no. 10010</p>	<p>For attaching the push button on the flat surfaces and line access from above or below.</p> 
<p><b>Metal protection guard</b> Item no. 11974-001 (Stainless steel) <b>Relief symbols</b> Item no. 13240</p>	<p>Tactile relief symbols can be installed in the protection guard on the right, left or on both sides.</p> 